

RMT and RET

Electronic/Electro-Mechanical Thermostats

providing accurate and reliable temperature control



- Danglett.
- RMT 230

- Available in Electronic and Electro-mechanical models
- Electronic versions available with
 LED status indicators
- Models available for 24V and 230V operation
- Large, easy to read scale
- · Locking and limiting as standard



OCC T



RMT and **RET**

Room Thermostats with Setting Dial



Providing accurate and reliable temperature control for a wide range of applications, from radiator based heating applications to underfloor heating.

RMT Electro-Mechanical Room Thermostats

A stylish range of electro-mechanical room thermostats for use in 24V and 230V systems. All models, with the exception of RMT230*, have an accelerator heater to improve control accuracy. Models are available with thermometer and night set-back facility, activated by an external time control

RET Electronic Room Thermostats

To complement the electromechanical models Danfoss Randall produce a range of electronic room thermostats, which have a matching style to that of the RMT. The RET range is based upon a wallplate construction, allowing for ease of installation.

The RET range of electronic thermostats are available in 24V and 230V versions. All models incorporate an electronic anticipator heater to improve thermal performance.

The thermostats are available in various configurations, including versions with voltage free contacts and LED status indication.

Included in the range are two special night set-back thermostats, which, by means of an external time clock, can be used to control overnight temperatures at a level 5K below normal day operation.

All RET24 and RET230 thermostats require a live and neutral power supply of the appropriate voltage.







RET230

RMT Electro-Mechanical Room Thermostats							
Туре	Code No.	Operating Voltage	Built-in Thermometer	5K Night Set-back (1)	Switch Type	Comments	
RMT230*	087N111000	230 Vac			SPDT	no accelerator	
RMT230	087N110000	230 Vac			SPDT		
RMT230T	087N112500	230 Vac	•	•	SPDT		
RMT24	087N119600	24 Vac			SPDT		
RMT24T	087N119700	24 Vac	•	•	SPDT		
(4) AP 1							


(1) Night set-back is achieved using external time control.

RET Electronic Room Thermostats							
Туре	Code No.	Operating Voltage	LED Status Indicators		Switch	Commonto	
			Power on (1)	Stat Calling (2)	Type	Comments	
RET230	087N700400	230 Vac		•	SPDT		
RET230L	087N700600	230 Vac	•	•	SPDT		
RET230VF2	087N700801	230 Vac	•	•	SPDT	Volt-free contacts	
RET230NSB	087N701000	230 Vac	•	•	SPDT	5K night set-back volt- free contacts (3)(4)	
RET24	087N701400	24 Vac		•	SPDT		
RET24VF	087N701600	24 Vac		•	SPDT	Volt-free contacts	
RET24NSB	087N701800	24 Vac		•	SPDT	5K night set-back volt- free contacts (4)(5)	

- (1) Power on indicator is lit when power is applied to thermostat.
- (2) Calling indicator is lit when thermostat relay is energised and calling for heat.
- (3) In night set-back version, power on LED changes colour during night set-back period.
- (4) Night set-back is achieved by using external time control.
- (5) Second LED is lit during night set-back periods.


(5) Second LED is lit during night set-back periods.							
Specifications		RMT24	RET230	RET24	RET230		
Switching differential		<1°C	<1°C	<1°C	<1°C		
Operating voltage (±15%)		24 Vac	230 Vac	24 Vac	230 Vac		
Contact rating		10 (4) A	10 (4) A	3 (1) A	3 (1) A		
Temperature		8-30°C	8-30°C	5-30°C	5-30°C		
Dimensions	Wide	80mm	80mm	85mm	85mm		
	High	80mm	80mm	86mm	86mm		
	Deep	40mm	40mm	42mm	42mm		

Wiring Details



RET230

RMT230



RET230 and RET230L

Danfoss Randall Ltd

Ampthill Road, Bedford, MK42 9ER, T: 0845 - 1217 400, F: 0845 - 1217 515